

TASKI® Tapi Defoam

Defoamer

Description

Defoamer recommended for use in spray extraction machines and wet vacuum cleaners. Prevents build up of foam in the pick up tank.

Key properties

- Fast defoaming action
- Suitable for all vacuum pick up tanks where foam control is required

Benefits

- Increases carpet cleaning efficiency
- Will not block machines due to foam development

Use instructions


Dosage:

TASKI Tapi Defoam is ready to use. For detailed information regarding the dosing, please refer to the technical data table. Proper dosage saves costs and minimises environmental impact.

Application

Pour approximately 100ml directly into the pick-up/dirty water tank of the machine.

C1g



© A.I.S.E.

TASKI[®] Tapi Defoam C1g

Defoamer

Technical data

Platform	SKU	Description/Pack size	RTU	Spray bottle	Bucket	Scrubber drier	Appearance	pH value neat	pH value in-use	Relative density (20°C)
Standard concentrate	7512368	TASKI Tapi Defoam 6 x 1 L	RTU	N/A	N/A	100 ml	Clear, colourless	N/A	N/A	0.80 g/cm ³ (20°C)

The above data is typical of production and should not be taken as specification.

Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet (SDS). <https://sds.sealedair.com/>
Only for professional users/specialists. Store in original closed containers away from extremes of temperature.

Product compatibility

Do not apply the product directly on the carpet (risks of staining from the solvents and fast re-soiling due to residues from the product).

Environmental information

Must not reach sewage water or drainage ditch undiluted or unneutralised.